



**DAY TANK LEVEL SENSOR**

LS-06-43-SS

DAY TANK LEVEL SENSOR UP TO 43" TANK - STAINLESS 316 CONSTRUCTION

FITTING: 2" NPT, Sq head, Solid, SS

ADJUSTABLE FITTING: SS compression fitting w/Delrin Ferule



- CONDUIT CONNECTION: 1/2" MNPT
- STEM: 1/2" DIA, SS, OAL equals L1 plus
- FLOAT: 1.3" x 1.6" (1513) SS SS Clips

SWITCH RATING: 20 Watts, SPST (L6 switch is 10 watts SPDT when shared float with L5)

WIRING: 25 ft Cable

L6 \_\_\_\_% \_\_\_\_" Return Pump Start, N.O. Violet and White

- L5 \_\_\_\_% \_\_\_\_" High Level, N.C. Gray (Black common)
- L4 \_\_\_\_% \_\_\_\_" Pump Stop N.C. Orange (Black Common)
- L3 \_\_\_\_% \_\_\_\_" Return Pump Stop, N.O. (Blue and Brown)
- L2 \_\_\_\_% \_\_\_\_" Pump Start, N.O. Yellow (Black Common)
- L1 \_\_\_\_% \_\_\_\_" Low Level, N.O. Red (Black Common)

WIRING CONFIG: L1, L2, L4 L5 share comm. black wire

- L3 and L6 wired individually
- Note: L5 L6 share a float when less then 2" separation
- Note: Dimensions are measured at full extension

[More Information](#)

