



**LIQUID LEVEL MONITOR - LLM-2 (2 Point)**

LLM-2

Liquid Level Monitor and leak-detection system provides continuous, accurate monitoring in a variety of applications. Typical applications are storage tanks, sumps, dry interstitial spaces and dispenser pans.

The Liquid Level Monitor - LLM-2 (2 Point) system can be used to monitor a wide variety of locations. The LLM-2 you can choose two for the standard list or you can tell us what type of location (or switch) you would like to monitor.

A Standard List of Points To Monitor are:

- Over Fill Alarm
- High High Level Alarm
- High Level Alarm
- High Level Warning
- Delivery Needed Warning
- Low Level Warning
- Low Level Alarm
- Tank Leak Alarm
- Piping Sump Leak Alarm



Specifications:

- NEMA 4x Enclosure - Suitable for Outdoor and High Corrosive Locations
- Suitable for Combustible products (Flammables Available Upon Request)
- Class 2, Div 2 Locations (Class 1, Div 1 Available Upon Request)
- UL 508A listed and meets NEC (NPFA70) and NFPA 30A requirements.



FOR GASOLINE OR FLAMMABLE CLASS 1 PRODUCTS AN IS-SAFE PACK MUST BE ADDED.



[More Information](#)

