



DPS-VFD 2HP 3PH 230

DPS-VFD

DUPLEX VARIABLE SPEED PUMP MOTOR SPEED CONTROLLER.

USED FOR MOTORS 1.4 HP TO 25 HP (DISPLAYED FOR 2 HP MOTORS DRIVES)

OPTIONS:

- SINGLE MOTOR APPLICATIONS
- TWO MOTOR APPLICATIONS
- SINGLE RUN SIGNAL WITH LEAD LAG PUMP CONTROL
- SINGLE RUN SIGNAL WITH ALTERNATING PUMP CONTROL
- MAIN PANEL DISCONNECT
- MOTOR CIRCUIT PROTECTION
- SINGLE PHASE INPUT
- THREE PHASE INPUT
- 120 VAC SINGLE PHASE INPUT
- 208/230 VAC SINGLE PHASE INPUT
- 208/230 VAC THREE PHASE INPUT
- 460 VAC THREE PHASE INPUT

SPECIFICATIONS:

- UL508A LISTED
- NENA 1 CARBON STEEL ENCLOSURE
- NENA 12 CARBON STEEL ENCLOSURE
- NENA 4 CARBON STEEL ENCLOSURE
- NENA 4X FIBERGLASS ENCLOSURE
- NENA 4X STAINLESS STEEL ENCLOSURE
- UP TO (2) 25 HORSE POWER 3 PHASE PUMP MOTORS
- CLASS 2 DIV 2 GROUPS B,C,D

[More Information](#)

