

Lakeside Petroleum Service

Spanning the Globe
with our Services



PetroPanels
Industrial Automation



ATG-ENC-OEL8000-2-HL

ATG-ENC-OEL8

ATG-ENC-OEL8000-2-HL

FOR OMNTEC OEL8000 NEMA 4X STAINLESS STEEL ENCLOSURE.

THE OEL 8000 PANEL IS NEMA 1 RATED FOR INDOOR USE ONLY. WHEN THE OEL8000 PANEL IS REQUIRED TO BE INSTALLED OUTSIDE A NEMA 4 RATED ENCLOSURE IS REQUIRED. WHEN THE ELEMENTS ARE HARSH IT IS BEST TO INSTALL THE OEL 8000 IN A NEMA 4X ENCLOSURE WITH AN INTERNAL HEATER SYSTEM. AN INTEGRATED WINDOW KIT ON THE ENCLOSURE MUST BE INSTALLED FOR VISUAL INSPECTION AND EVERY DAY USAGE. AN INTERNAL LIGHT AND DOOR SWITCH IS ALSO INSTALLED TO ENSURE 24/7 OPERATIONS.

THE ENCLOSURE COMES WITH PREINSTALLED CONDUITS AND WIRING INSIDE THE ENCLOSURE FOR EASY INSTALLATION. TYPICALLY NO PENETRATIONS IN THE STAINLESS STEEL ENCLOSURE ARE REQUIRED.



SYSTEM BENEFITS:

- NEMA 4X 24*24*8 SS304 ENCLOSURE
- MODIFIED BACK PANEL ENCLOSURE
- INTEGRATED WINDOW KIT
- 80 W HEATER AND THERMOSTAT
- INTERNAL LIGHT WITH DOOR SWITCH
- PREINSTALLED ELECTRICAL CONDUITS INSIDE ENCLOSURE



SPECIFICATIONS:

- NEMA 4X STAINLESS STEEL 304
- SUITABLE FOR OUTDOOR USE
- SUITABLE FOR CLASS 2 DIVISION 2 LOCATIONS
- SUITABLE FOR HIGH CORROSION AREAS
- SUITABLE FOR COLD WEATHER LOCATIONS



[More Information](#)